## باديعوت الفطيه **☆** Al-futtaim **B**odycote

محبص البهواد Materials Testing

ether with the co AND THE STREET

## REPORT OF TESTS

Description	One Sample of Plywood		
Tested for	Procure IT Direct., Post Box No.1 (2950, Dubai, U.A.F.		
f.ab Ref. No.	WR07-66451 (Page 1 of 1)	Request No.	WQ07-23480
Date Received	24.12.2007	Date Reported	29.12.2007

Client's reference

Requisition dated 24.12.2007

Sample reference

Plywood

AFBT sample No.

W07-023480/01

## Introduction

Further to the test work instructions received from M/s. Procure IT Direct., Dubai, dated 24.12.2007, one sample of Strand hoard provided has been tested for the following by Al Futtaim Bodycote Texting LLC;

## 2.0 **Bond Performance Test**

Test Method: Test was carried out in general accordance with BS 6500: 1985

Rectangular specimens with dimensions of 6 inch x 6 inch were prepared from the supplied sample and submerged in boiling water under normal conditions for 72±3 hours. Then the specimens were immersed in water @ 15±5°C until cooled. After conditioning, the specimens were examined for any kind of bond failure.

Test	Ohservasion
Rond Test	No sign of bond failure, glue failure or any other defects.

and on behalf of Al Furtain mayene Testing (L.L.C) Tested by : KSLN , Date tested : 26.12.2007-29.12.2007

Sampled by the client, contificate of sampling was not given. This rependent only be reproduced in full. Approval of the testing theretay is a

iples will be remined for a period of one month unity, index oth lest results reline only to the xamples lested.

Al-Tentrain Bodycote ادبكوت تيستيدغ (دمم) P.O. Box: 34924 - DUBAT - U A.E.